

LOOX LED DRIVER

CONSTANT VOLTAGE 24 V

REALLY FLAT

24 V SYSTEM

!

- 1** Cat. No. 833.77.900
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 15 \text{ W}$
- 2** Cat. No. 833.77.912
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 20 \text{ W}$
- 3** Cat. No. 833.77.901
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 30 \text{ W}$
- 4** Cat. No. 833.77.914
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 75 \text{ W}$

Parallel connection

The driver is the heart of the Loox system, and is suitable for connecting to all of the world's most frequently used power systems. It has an integrated switching function and connections for all of the most popular types of switch.

! > Lead length from driver to switch max. 6 m.

Cat. No.	833.77.900 1	833.77.912 2	833.77.901 3	833.77.914 4
Wattage (W)	0 – 15	0 – 20	0 – 30	0 – 75
Input voltage	100 – 240 V; 50 – 60 Hz	100 – 240 V; 50 – 60 Hz	100 – 240 V; 50 – 60 Hz	100 – 240 V; 50 – 60 Hz
Output voltage	DC 24 V	DC 24 V	DC 24 V	DC 24 V
Output current	0.625 A	0.83 A	1.25 A	3.15 A
Degree of protection	IP20	IP20	IP20	IP20
Number of slots	6 slots for 24 V lights, 1 slot for switch, 1 slot for country-specific primary lead			
Colour	Black	Black	Black	Black
Length (mm)	140	128	195	208
Width (mm)	43	50,5	43	56,5
Height (mm)	20	14	28	30
Supplied with	1 driver with mounting accessories			

Country-specific primary leads – lead length 2 m

Cat. No.	833.89.000	833.89.001	833.89.002	833.89.003	833.89.004	833.89.005	833.89.006	833.89.007	833.89.009	833.89.050
Plug design										
Designation	UK	AU	EU	US	JP	CN	KR	TW	EU	US
Supplied with	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece